

# thm\_2ErrorStateMonad\_2EAPPLY\_\_UNIT\_\_UNIT (TMPiqD2kESxkdYxDVwKRftW5PWJTgHivcwo)

October 26, 2020

**Definition 1** We define  $c\_2Emin\_2E\_3D$  to be  $\lambda A.\lambda x \in A.\lambda y \in A.inj\_o (x = y)$  of type  $\iota \Rightarrow \iota$ .

**Definition 2** We define  $c\_2Ebool\_2ET$  to be  $(ap (ap (c\_2Emin\_2E\_3D (2^2)) (\lambda V0x \in 2.V0x)) (\lambda V1x \in 2.V1x))$

**Definition 3** We define  $c\_2Emin\_2E\_3D\_3D\_3E$  to be  $\lambda P \in 2.\lambda Q \in 2.inj\_o (p \Rightarrow q)$  of type  $\iota$ .

**Definition 4** We define  $c\_2Ebool\_2E\_21$  to be  $\lambda A\_27a : \iota.(\lambda V0P \in (2^{A\_27a}).(ap (ap (c\_2Emin\_2E\_3D (2^{A\_27a}))$

**Definition 5** We define  $c\_2Ebool\_2E\_2F\_5C$  to be  $(\lambda V0t1 \in 2.(\lambda V1t2 \in 2.(ap (c\_2Ebool\_2E\_21 2) (\lambda V2t \in 2.V2t)))$

Let  $ty\_2Epair\_2Eprod : \iota \Rightarrow \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A0.nonempty A0 \Rightarrow \forall A1.nonempty A1 \Rightarrow nonempty (ty\_2Epair\_2Eprod A0 A1) \quad (1)$$

Let  $c\_2Epair\_2EABS\_prod : \iota \Rightarrow \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A\_27a.nonempty A\_27a \Rightarrow \forall A\_27b.nonempty A\_27b \Rightarrow c\_2Epair\_2EABS\_prod A\_27a A\_27b \in ((ty\_2Epair\_2Eprod A\_27a A\_27b)^{(2^{A\_27b})^{A\_27a}}) \quad (2)$$

**Definition 6** We define  $c\_2Epair\_2E\_2C$  to be  $\lambda A\_27a : \iota.\lambda A\_27b : \iota.\lambda V0x \in A\_27a.\lambda V1y \in A\_27b.(ap (c\_2E$

Let  $ty\_2Eone\_2Eone : \iota$  be given. Assume the following.

$$nonempty ty\_2Eone\_2Eone \quad (3)$$

Let  $ty\_2Esum\_2Esum : \iota \Rightarrow \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A0.nonempty A0 \Rightarrow \forall A1.nonempty A1 \Rightarrow nonempty (ty\_2Esum\_2Esum A0 A1) \quad (4)$$

Let  $c\_2Esum\_2EABS\_sum : \iota \Rightarrow \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow c\_2Esum\_2EABS\_sum\ A\_27a\ A\_27b \in ((ty\_2Esum\_2Esum\ A\_27a\ A\_27b)^{((2^{A\_27b})^{A\_27a})^2}) \quad (5)$$

**Definition 7** We define  $c\_2Esum\_2EINL$  to be  $\lambda A\_27a : \iota.\lambda A\_27b : \iota.\lambda V0e \in A\_27a.(ap\ (c\_2Esum\_2EABS\_sum\ V0e))$

Let  $ty\_2Eoption\_2Eoption : \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A0.nonempty\ A0 \Rightarrow nonempty\ (ty\_2Eoption\_2Eoption\ A0) \quad (6)$$

Let  $c\_2Eoption\_2Eoption\_ABS : \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow c\_2Eoption\_2Eoption\_ABS\ A\_27a \in ((ty\_2Eoption\_2Eoption\ A\_27a)^{(ty\_2Esum\_2Esum\ A\_27a\ ty\_2Eone\_2Eone)}) \quad (7)$$

**Definition 8** We define  $c\_2Eoption\_2ESOME$  to be  $\lambda A\_27a : \iota.\lambda V0x \in A\_27a.(ap\ (c\_2Eoption\_2Eoption\_ABS\ V0x))$

**Definition 9** We define  $c\_2ErrorStateMonad\_2EUNIT$  to be  $\lambda A\_27a : \iota.\lambda A\_27b : \iota.\lambda V0x \in A\_27b.(\lambda V1s \in A\_27a.V1s)$

Let  $c\_2Epair\_2ESND : \iota \Rightarrow \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow c\_2Epair\_2ESND\ A\_27a\ A\_27b \in (A\_27b)^{(ty\_2Epair\_2Eprod\ A\_27a\ A\_27b)} \quad (8)$$

Let  $c\_2Epair\_2EFST : \iota \Rightarrow \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow c\_2Epair\_2EFST\ A\_27a\ A\_27b \in (A\_27a)^{(ty\_2Epair\_2Eprod\ A\_27a\ A\_27b)} \quad (9)$$

**Definition 10** We define  $c\_2Epair\_2Epair\_CASE$  to be  $\lambda A\_27a : \iota.\lambda A\_27b : \iota.\lambda A\_27c : \iota.\lambda V0p \in (ty\_2Epair\_2Epair\ A\_27a\ A\_27b\ A\_27c).V0p$

**Definition 11** We define  $c\_2Emin\_2E\_40$  to be  $\lambda A.\lambda P \in 2^A.\text{if } (\exists x \in A.p\ (ap\ P\ x)) \text{ then } (the\ (\lambda x.x \in A \wedge P\ x)) \text{ of type } \iota \Rightarrow \iota.$

**Definition 12** We define  $c\_2Eone\_2Eone$  to be  $(ap\ (c\_2Emin\_2E\_40\ ty\_2Eone\_2Eone))\ (\lambda V0x \in ty\_2Eone\_2Eone.V0x)$

**Definition 13** We define  $c\_2Ebool\_2EF$  to be  $(ap\ (c\_2Ebool\_2E\_21\ 2))\ (\lambda V0t \in 2.V0t)$ .

**Definition 14** We define  $c\_2Ebool\_2E\_7E$  to be  $(\lambda V0t \in 2.(ap\ (ap\ c\_2Emin\_2E\_3D\_3D\_3E\ V0t)\ c\_2Ebool\_2EF))$

**Definition 15** We define  $c\_2Esum\_2EINR$  to be  $\lambda A\_27a : \iota.\lambda A\_27b : \iota.\lambda V0e \in A\_27b.(ap\ (c\_2Esum\_2EABS\_sum\ V0e))$

**Definition 16** We define  $c\_2Eoption\_2ENONE$  to be  $\lambda A\_27a : \iota.(ap\ (c\_2Eoption\_2Eoption\_ABS\ A\_27a))\ (c\_2Eone\_2Eone)$

Let  $c\_2Eoption\_2Eoption\_CASE : \iota \Rightarrow \iota \Rightarrow \iota$  be given. Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow c\_2Eoption\_2Eoption\_CASE\ A\_27a\ A\_27b \in (((A\_27b)^{(A\_27b^{A\_27a})})^{A\_27b})^{(ty\_2Eoption\_2Eoption\ A\_27a)} \quad (10)$$

**Definition 17** We define  $c\_2ErrorStateMonad\_2EBIND$  to be  $\lambda A\_27a : \iota.\lambda A\_27b : \iota.\lambda A\_27c : \iota.\lambda V0g \in ((ty\_$

**Definition 18** We define  $c\_2ErrorStateMonad\_2EES\_APPLY$  to be  $\lambda A\_27a : \iota.\lambda A\_27b : \iota.\lambda A\_27c : \iota.\lambda V0f \in M$

Assume the following.

$$True \quad (11)$$

Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow (\forall V0t \in 2.((\forall V1x \in A\_27a.(p\ V0t)) \Leftrightarrow (p\ V0t))) \quad (12)$$

Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow (\forall V0x \in A\_27a.((V0x = V0x) \Leftrightarrow True)) \quad (13)$$

Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow (\forall V0f \in (A\_27b^{A\_27a}).(\forall V1g \in (A\_27b^{A\_27a}).((V0f = V1g) \Leftrightarrow (\forall V2x \in A\_27a.((ap\ V0f\ V2x) = (ap\ V1g\ V2x)))))) \quad (14)$$

Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow (\forall V0v \in A\_27b.(\forall V1f \in (A\_27b^{A\_27a}).((ap\ (ap\ (ap\ (c\_2Eoption\_2Eoption\_CASE\ A\_27a\ A\_27b)\ (c\_2Eoption\_2ENONE\ A\_27a))\ V0v)\ V1f) = V0v))) \wedge (\forall V2x \in A\_27a.(\forall V3v \in A\_27b.(\forall V4f \in (A\_27b^{A\_27a}).((ap\ (ap\ (ap\ (c\_2Eoption\_2Eoption\_CASE\ A\_27a\ A\_27b)\ (ap\ (c\_2Eoption\_2ESOME\ A\_27a)\ V2x))\ V3v)\ V4f) = (ap\ V4f\ V2x)))))) \quad (15)$$

Assume the following.

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow \forall A\_27c.nonempty\ A\_27c \Rightarrow (\forall V0x \in A\_27b.(\forall V1y \in A\_27c.(\forall V2f \in ((A\_27a^{A\_27c})^{A\_27b}).((ap\ (ap\ (c\_2Epair\_2Epair\_CASE\ A\_27a\ A\_27b\ A\_27c)\ (ap\ (ap\ (c\_2Epair\_2E\_2C\ A\_27b\ A\_27c)\ V0x)\ V1y))\ V2f) = (ap\ (ap\ V2f\ V0x)\ V1y)))))) \quad (16)$$

**Theorem 1**

$$\forall A\_27a.nonempty\ A\_27a \Rightarrow \forall A\_27b.nonempty\ A\_27b \Rightarrow \forall A\_27c.nonempty\ A\_27c \Rightarrow (\forall V0f \in (A\_27b^{A\_27c}).(\forall V1x \in A\_27c.((ap\ (ap\ (c\_2ErrorStateMonad\_2EES\_APPLY\ A\_27a\ A\_27b\ A\_27c)\ (ap\ (c\_2ErrorStateMonad\_2EUNIT\ A\_27a\ (A\_27b^{A\_27c}))\ V0f))\ (ap\ (c\_2ErrorStateMonad\_2EUNIT\ A\_27a\ A\_27c)\ V1x)) = (ap\ (c\_2ErrorStateMonad\_2EUNIT\ A\_27a\ A\_27b)\ (ap\ V0f\ V1x))))))$$