

t21_qc_lang3 (TMPFN- poTDk9SF23K52PzobygiUXNS81R1RZ)

October 27, 2020

Let $m1_qc_lang1 : \iota \Rightarrow o$ be given. Let $m1_subset_1 : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $k9_qc_lang1 : \iota \Rightarrow \iota$ be given. Let $v6_qc_lang1 : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $k13_qc_lang1 : \iota \Rightarrow \iota \Rightarrow \iota$ be given. Let $k24_qc_lang1 : \iota \Rightarrow \iota \Rightarrow \iota$ be given. Let $k1_xboole_0 : \iota$ be given. Assume the following.

$$\forall X0.(m1_qc_lang1 X0) \Rightarrow (\forall X1.(m1_subset_1 X1 (k9_qc_lang1 X0)) \Rightarrow (k24_qc_lang1 X0 (k13_qc_lang1 X0 X1) = k24_qc_lang1 X0 X1)) \quad (1)$$

Assume the following.

$$\forall X0.\forall X1.((m1_qc_lang1 X0) \wedge (m1_subset_1 X1 (k9_qc_lang1 X0))) \Rightarrow (m1_subset_1 (k13_qc_lang1 X0 X1) (k9_qc_lang1 X0)) \quad (2)$$

Assume the following.

$$\forall X0.(m1_qc_lang1 X0) \Rightarrow (\forall X1.(m1_subset_1 X1 (k9_qc_lang1 X0)) \Rightarrow ((v6_qc_lang1 X1 X0) \Leftrightarrow (k24_qc_lang1 X0 X1 = k1_xboole_0))) \quad (3)$$

Theorem 1

$$\forall X0.(m1_qc_lang1 X0) \Rightarrow (\forall X1.(m1_subset_1 X1 (k9_qc_lang1 X0)) \Rightarrow ((v6_qc_lang1 X1 X0) \Leftrightarrow (v6_qc_lang1 (k13_qc_lang1 X0 X1) X0)))$$