

t45_zf_lang1
(TMafvn3KcwajZsfsLPtQRw8iVjDqpHotkuT)

October 27, 2020

Let $v1_zf_lang : \iota \Rightarrow o$ be given. Let $m2_finseq_1 : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $k5_numbers : \iota$ be given. Let $r3_zf_lang : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $r1_zf_lang : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $r2_zf_lang : \iota \Rightarrow \iota \Rightarrow o$ be given. Assume the following.

$$\begin{aligned} & \forall X0.((v1_zf_lang X0) \wedge (m2_finseq_1 X0 k5_numbers)) \Rightarrow (\forall X1. \\ & ((v1_zf_lang X1) \wedge (m2_finseq_1 X1 k5_numbers)) \Rightarrow (\forall X2. (\\ & (v1_zf_lang X2) \wedge (m2_finseq_1 X2 k5_numbers)) \Rightarrow ((\neg(\neg(r3_zf_lang \\ & X0 X1) \wedge (r2_zf_lang X1 X2)) \wedge (\neg(r2_zf_lang X0 X1) \wedge (r3_zf_lang \\ & X1 X2)) \wedge (\neg(r2_zf_lang X0 X1) \wedge (r1_zf_lang X1 X2)) \wedge (\neg(r1_zf_lang \\ & X0 X1) \wedge (r2_zf_lang X1 X2)) \wedge (\neg(r3_zf_lang X0 X1) \wedge (r1_zf_lang \\ & X1 X2)) \wedge (\neg(r1_zf_lang X0 X1) \wedge (r3_zf_lang X1 X2)))))) \Rightarrow (r3_zf_lang \\ & X0 X2)))) \end{aligned} \tag{1}$$

Assume the following.

$$\begin{aligned} & \forall X0.((v1_zf_lang X0) \wedge (m2_finseq_1 X0 k5_numbers)) \Rightarrow (\forall X1. \\ & ((v1_zf_lang X1) \wedge (m2_finseq_1 X1 k5_numbers)) \Rightarrow ((r3_zf_lang \\ & X0 X1) \Leftrightarrow ((r2_zf_lang X0 X1) \wedge (X0 \neq X1)))) \end{aligned} \tag{2}$$

Theorem 1

$$\begin{aligned} & \forall X0.((v1_zf_lang X0) \wedge (m2_finseq_1 X0 k5_numbers)) \Rightarrow (\forall X1. \\ & ((v1_zf_lang X1) \wedge (m2_finseq_1 X1 k5_numbers)) \Rightarrow (\neg(r3_zf_lang \\ & X0 X1) \wedge (r1_zf_lang X1 X0))) \end{aligned}$$