

t4_conlat_1

(TMTF7aZBKmq8ktukZsSB2E9uYGRpYdgu6vq)

October 27, 2020

Let $v1_conlat_1 : \iota \Rightarrow o$ be given. Let $l1_conlat_1 : \iota \Rightarrow o$ be given. Let $m1_subset_1 : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $k1_zfmisc_1 : \iota \Rightarrow \iota$ be given. Let $u4_struct_0 : \iota \Rightarrow \iota$ be given. Let $r1_tarski : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $k3_funct_2 : \iota \Rightarrow \iota \Rightarrow \iota \Rightarrow \iota \Rightarrow \iota$ be given. Let $k9_setfam_1 : \iota \Rightarrow \iota$ be given. Let $u1_struct_0 : \iota \Rightarrow \iota$ be given. Let $k2_conlat_1 : \iota \Rightarrow \iota$ be given. Let $v1_funct_1 : \iota \Rightarrow o$ be given. Let $v1_funct_2 : \iota \Rightarrow \iota \Rightarrow o$ be given. Let $k2_zfmisc_1 : \iota \Rightarrow \iota \Rightarrow \iota$ be given. Let $r1_conlat_1 : \iota \Rightarrow \iota \Rightarrow o$ be given. Assume the following.

$$\begin{aligned} \forall X0. (&(\neg v1_conlat_1 X0) \wedge (l1_conlat_1 X0)) \Rightarrow ((v1_funct_1 \\ &(k2_conlat_1 X0)) \wedge ((v1_funct_2 (k2_conlat_1 X0) (k9_setfam_1 \\ &(u4_struct_0 X0)) (k9_setfam_1 (u1_struct_0 X0))) \wedge (m1_subset_1 \\ &(k2_conlat_1 X0) (k1_zfmisc_1 (k2_zfmisc_1 (k9_setfam_1 (u4_struct_0 \\ &X0)) (k9_setfam_1 (u1_struct_0 X0)))))) \end{aligned} \tag{1}$$

Assume the following.

$$\begin{aligned} \forall X0. (&(\neg v1_conlat_1 X0) \wedge (l1_conlat_1 X0)) \Rightarrow (\forall X1. \\ &(((v1_funct_1 X1) \wedge ((v1_funct_2 X1 (k9_setfam_1 (u4_struct_0 X0)) \\ &(k9_setfam_1 (u1_struct_0 X0))) \wedge (m1_subset_1 X1 (k1_zfmisc_1 \\ &(k2_zfmisc_1 (k9_setfam_1 (u4_struct_0 X0)) (k9_setfam_1 (u1_struct_0 \\ &X0)))))) \Rightarrow ((X1 = k2_conlat_1 X0) \Leftrightarrow (\forall X2. (m1_subset_1 X2 \\ &(k1_zfmisc_1 (u4_struct_0 X0)) \Rightarrow (k3_funct_2 (k1_zfmisc_1 (u4_struct_0 \\ &X0) (k9_setfam_1 (u1_struct_0 X0)) X1 X2 = ReplSep (toset (\lambda X3 : \\ &\iota. m1_subset_1 X3 (u1_struct_0 X0))) (\lambda X3 : \iota. \forall X4. \\ &(m1_subset_1 X4 (u4_struct_0 X0)) \Rightarrow ((X4 \in X2) \Rightarrow (r1_conlat_1 X0 X3 \\ &X4)) (\lambda X3 : \iota. X3)))))) \end{aligned} \tag{2}$$

Assume the following.

$$\forall X0. \forall X1. (r1_tarski X0 X1) \Leftrightarrow (\forall X2. (X2 \in X0) \Rightarrow (X2 \in X1)) \tag{3}$$

Theorem 1

$$\begin{aligned} & \forall X0.((\neg v1_conlat_1 X0) \wedge (l1_conlat_1 X0)) \Rightarrow (\forall X1. \\ & (m1_subset_1 X1 (k1_zfmisc_1 (u4_struct_0 X0))) \Rightarrow (\forall X2. \\ & (m1_subset_1 X2 (k1_zfmisc_1 (u4_struct_0 X0))) \Rightarrow ((r1_tarski \\ & X1 X2) \Rightarrow (r1_tarski (k3_funct_2 (k1_zfmisc_1 (u4_struct_0 X0)) \\ & (k9_setfam_1 (u1_struct_0 X0)) (k2_conlat_1 X0) X2) (k3_funct_2 \\ & (k1_zfmisc_1 (u4_struct_0 X0)) (k9_setfam_1 (u1_struct_0 X0)) \\ & (k2_conlat_1 X0) X1)))))) \end{aligned}$$